

SK3323J/3325J Programmable DC Power Supply



Features

- Three outputs, the maximum power is up to 338W
- Lowe Ripple and Noise: $\leq 1\text{mV}/\leq 3\text{mA}$
- Standard Timing Output
- Comprehensive over-voltage and over-temperature protection
- Fully remote control interface: LAN, USB Device and RS-232
- 5 digit LED display can show voltage, current and power simultaneously

Specification

Model	SK3323J	SK3325J
Channel		
CH1	0~32V/0~3A	0~32V/0~5A
CH2	0~32V/0~3A	0~32V/0~5A
CH3	0~6V/0~3A	
Line Regulation		
Voltage	CH1, CH2, CH3	$\leq 1 \times 10^{-4} + 3\text{mV}$
Current	CH1, CH2, CH3	$\leq 1 \times 10^{-4} + 500\mu\text{A}$
Load Regulation		
Voltage	CH1	$\leq 1 \times 10^{-4} + 3\text{mV}$
	CH2	$\leq 1 \times 10^{-4} + 5\text{mV}$
	CH3	$\leq 1 \times 10^{-4} + 3\text{mV}$
Current	CH1, CH2, CH3	$\leq 1 \times 10^{-4} + 500\mu\text{A}$
Programming/Readback Accuracy		
Voltage	CH1 CH2 CH3	$\leq (0.05\% + 20\text{mV})$
Current	CH1 CH2 CH3	$\leq (0.3\% + 5\text{mA})$
		$\leq (2\% + 10\text{mA})$
Ripple and Noise		
Voltage		$\leq 1\text{mV}$
Current		$\leq 3\text{mA}$
Display resolution		
Voltage		1mV
Current		1mA
Display Digits		
Voltage		5 digits
Current		4 digits
Other function		
Auto switch of serial and parallel	○	
Timing Output	●	
OTP	●	
OVP	●	
General Characteristics		
Rated Voltage	220/230 (198-242)V	
Rated Power	0.5kW 0.7kVA	0.6kW 0.8kVA
Rated Frequency	50/60(47-63) Hz	
USB charging Interface	5V 2A	
Remote Interface	LAN, USB Device, RS-232	
Dimension	256×160×440mm	
Weight	9KGs	10KGs

Standard Accessories

Power Cord	1
CD(User's Guide)	1