

# S-MicroW XL

S-MicroW XL is a temperature data logger from -80°C to 140°C (calibration from 25°C to 140°C) with 20 or 50 or 100 or 150 mm or on demand length external probe (probes cannot be switched) on a 5 mm base (base height is not counted for probe length), managed with Windows software and USB interface (DiskInterface HS, Multibay).

**Battery is user replaceable** and the data logger is **provided with an Accredia (NIST equivalent) traceable certificate** on 6 points.

The other versions of the data logger are:

- S-MicroW XL Flexible: with flexible cable probe and rigid probe at the end
- S-MicroW XL Bendable: with semi-rigid metal bendable probe and rigid probe at the end
- S-MicroW XL Ultra Freeze: includes calibration points from -40°C for use also from -80°C with high accuracy

For each version it is available the L model too, S-MicroW L, which has same diameter but a smaller battery: less battery life but reduced size.

There are also other models of high temperature data loggers, for pressure and humidity too.



## Main features

- With different lengths rigid probe for penetration
- Completely food grade and waterproof
- **All software calculate lethality value (F0, PU, A0 ecc.)**
- Low battery consumption for an extended battery life
- User replaceable battery (**software shows battery status**)
- Very easy to deploy in any type of package
- Accredia (NIST equivalent) traceable calibration certificate included
- Available **extended calibration from -80°C** (order extra calibration points)

## Plus

- Extremely high accuracy and precision: with an accuracy of  $\pm 0,1^{\circ}\text{C}$  these devices can be employed in any application involving pharmaceuticals, validation, laboratory and medical field
- High accuracy even outside the calibration range
- Fast response time thanks to the 3 mm diameter probe
- Printed reports compliant with health regulations and ISO (data are not editable in the software)

## The system

The system is made up by:

- S-MicroW XL temperature data logger
- DiskInterface HS or Universal Multibay
- SPD software or TS Manager software (compatible with the FDA 21 CFR Part 11 regulation)

## Accessories

- SPD
- Tacky thermal pad

## Applications



Validation



Sterilisation



Pharmaceutical



Healthcare



Medical



Laboratories



Food & Beverages



Pasteurisation

- DiskInterface HS
- Universal multibay
- Locking bolt
- Fastening system
- S-Micro XL heat protection 1
- S-Micro XL heat protection 2
- P-Micro XL, S-Micro XL, S-MicroW XL, RHTemp 80 XL, RHTemp 125 XL battery kit

## Technical specifications

Dimensions	64 h X 21 Ø (mm)
Probe dimensions	Probe base dimensions 5 h X 14 Ø (mm) - Probe 20/50/100/150 l X 3 Ø (mm) - Probe l on demand X 3 Ø (mm) (l on demand: min. 6 mm / max. 175 mm. For longer probes ask for quotation)
Weight	61 gr
Materials	Stainless steel AISI316L, PEEK
Temperature range	-80 °C ÷ +140 °C
Standard calibration points (temperature)	25/50/75/100/125/140°C
Extra calibration points (temperature)	Within the range -80 °C ÷ +140 °C
Temperature resolution	0,01 °C
Temperature accuracy	± 0,1 °C (valida nel range di calibrazione)
Memory (n. of acquisitions)	20.224
Acquisition step	From 1 every second up, with 1 second steps
Protection degree	IP68
Battery life	+17.000.000 acquisizioni ad 1 secondo in continuo (tempo stimato @ 25°C. La vita della batteria è più breve a basse ed alte temperature)
Software&Mobile App	SPD, TS Manager
Accessories	DiskInterface HS, Multibay universale



**Tecnosoft srl**  
Via Galvani, 4, 20068, Peschiera Borromeo (MI), Italy  
T: (+39) 02 2692 2888 - F: (+39) 02 2692 2875  
email: [info@tecnosoft.eu](mailto:info@tecnosoft.eu) - web: [www.tecnosoft.eu](http://www.tecnosoft.eu)  
UNI EN ISO 9001:2008 Certiquality/IQNet N. 17733

