

# Additel 936 Hydraulic High Pressure Calibration Pump



- Generate 85% vacuum to 15,000 psi (1,000 bar) pressure
- Minimal maintenance
- Increase and decrease pressure smoothly
- Three pressure ports
- Hand-tight quick connectors

**Distributor Indonesia**  
**PT TRIWI PUTRA JAYA**  
 Taman Surya 3.H7.N0.17 Jl. Daan Mogot  
 Pegadungan – Kalideres, Jakarta 11830  
 ☎ +62 21 541 7194 Fax. +62 21 451 4630  
 ☒ +62 818 920 386 - +62 822 9908 5294  
 ☑ +62 818 920 386 - +62 822 9908 5294  
 ✉ info@trwi-online.com / sales@pttrwi.com  
 🌐 www.trwi-online.com / www.pttrwi.com



## OVERVIEW

The 936 Hydraulic High Pressure Test Pump is a hand operated pressure pump designed to generate pressure from 85% vacuum to 15,000 psi (1,000 bar). With the patented screw press technology, high pressures can be easily generated, as well as increased and decreased smoothly. A specially designed shut-off valve makes the pressure as stable as possible during calibration. With no check valve (non-returning valve), the 936 avoids the troublesome leakage issues that is usually experienced with hand pumps and allows for minimal maintenance. Three hand-tight quick connectors installed on the pump allow easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches. The 936 is an ideal comparison test pump for calibrating pressure measuring instruments such as test gauges, indicators or transducers in the laboratory.

## FEATURES

- **High Pressure**  
Generates pressure up to 15,000 psi (1000 bar)
- **Durable and Minimal Maintenance**  
Patented screw press technology, without non-returning valve inside that is usually used on troublesome hand pumps.
- **Easy-to-use**  
High pressures can be generated easily, as well as increased and decreased smoothly.
- **Extremely Low Leakage**  
Patented screw press technology replaces troublesome check valves (non-returning valve) in most hand pumps which practically eliminates leakage.
- **Hand-tight Quick Connectors**  
Allows easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches.

## SPECIFICATIONS

- **Media:** Oil
- **Reservoir capacity:** 420 ml (25.6 in<sup>3</sup>)
- **Pressure Range**  
85% vacuum to 15,000 psi (1,000 bar) positive.
- **Material**  
Ram/adapters: SS  
Body: SS/aluminum  
Seals: Buna-N, PTFE, Copper Alloy, SS
- **Connection**  
Hand-tight connectors for both test gauge and reference gauge(s).  
1/4NPT female, 1/2NPT female, 1/4BSP female, 1/2BSP female, or M20X1.5 female
- **Dimensions**  
Height: 9.1" (230 mm)  
Base: 20.5" (520 mm) x 14.2" (360 mm)
- **Weight:** 35.2 lb (16 kg).
- **Warranty:** 1 year
- **Piston volume**  
Low pressure piston: 30 ml (1.8 in<sup>3</sup>)  
High pressure piston: 2.5 ml (0.15 in<sup>3</sup>)

## ORDERING INFORMATION

- **Model Number**



Model

**Pressure port type:**  
 N - 1/4NPT female  
 N2 - 1/2NPT female  
 B - 1/4BSP female  
 B2 - 1/2BSP female  
 M - M20X1.5 female

**SET:** Pump and carrying case included

- **Accessories included**

Mineral oil, 1 bottle (250 ml)  
 O-ring: 20 pcs    Manual: 1 pc  
 Carrying case (936-X-SET models only)

- **Optional Accessories**

Model number	Description
9202	Oil, Mineral Oil, 1 liter (1 quart)
ADT102	Adapters and fittings, 1/4NPT male to various male and female connection (25 pcs).
ADT103	Adapters and fittings, 1/4NPT (1/2NPT, 1/4BSP, 1/2BSP, or M20X1.5) male to various female hand-tight quick connectors (10 pcs).
9908	Carrying case for 936, 937, 938 or 949.
ADT936-MK	Maintenance kit for Additel 936 pump